ANK FUEL APPROVED

containment basin 110%



Tutte le immagini sono meramente a scopo illustrativo. L'azienda si riserva di apportare gualsiasi tipo di modifica senza alcuna comunicazione e/o autorizzazione preliminare

DIMENSION/WEI	GHT					
Code	Capacity	Diameter	Lenght	Basin dimension	Roof dimension	Weight Kg
PFTF-3C70BS/A1X	3.000 liters	1.500 mm	1.840 mm	1650x2400xh870mm	1800x2500mm	610 Kg
PFTF-5C70BS/A1X	4.992 liters	1.800 mm	2.150 mm	2250x2430xh1050mm	2350x2500mm	815 Kg
PFTF-7C70BS/A1X	7.000 liters	1.800 mm	2.900 mm	2250x3260xh1050mm	2350x3500mm	991 Kg
PFTF-9C70BS1X	9.000 liters	1.800 mm	3.660 mm	2160x4100xh1120mm	2350x4400mm	1140 Kg

CUDE7OMC B.SMART

Diesel Tanks, TANK FUEL CUBE 70B.SMART 1X, homologated by the Ministry of Internal Affairs according to Italian law 3704/1366/80/37/44), D.M. 19/03/90 and D.M. 22 November 2017.

Steel tanks for Diesel fuel storage and delivery, homologated by Italian Ministry of Interior. Horizontal cylindrical mono-skin tanks manufactured by using shell plates and dished endsmade of carbon steel quality S235JR according to UNI EN 10025, watertight electro-welded(submerged arc welding process), provided with anti-roll supports, primed with a rustpreventing layer and externally treated with two coats of primer and a final finish of twocoatings of synthetic metallic GREY paint. Tanks are delivered pressure-tested and ready to use. Equipment: collection basin able to hold 110% of total quantity of the tank, bottom discharge with cap, 1"suction hose with no-return valve and calibrated spring, suction filter, 1"ball valve, manhole 400mm diameter with a 3-inch opening with a lockable brass bayonet fastening and a 90% load limiting valve, 1" 1/2 vent with brass fire-barrier terminal, mechanical floating level indicator, minimum level pump locking device, electric panel, plug for the connection of the earth cable, service ladder (with non-slip steps, handrail for TF 5.000-7000-9000 or grab handle for TF 1200-2000-3000). A protection roof isavailable (as option) made of a tubular metal galvanised profile and cover. A water separator filter is also available for all versions (as option)

Electronic delivery group



CUBE 70 B.SMART Electronic delivery group with nominal flow rate 70 lt / min, equipped with self-priming pump with built-in filter, digital flow meter with +/- 0.5% accuracy, delivery hose mt. 4, automatic dispensing noozle and minimum level pump

block. in real time.

Communication between CUBE B.SMART, Phone App and Cloud Software is very simple. Once the B.SMART App is open, the Android or iOS mobile device automatically connects to the diesel dispenser to allow the driver to refuel. During delivery, the driver can monitor the quantity dispensed directly on the mobile device and, once completed, can view the virtual receipt, which will be sent in real time to the web app.

The fleet manager will be able to monitor all the deliveries in real time, through the simple and immediate graphic interface of the Software Cloud.

The basic version includes 10 accesses (drivers) expandable in packages of 10 accesses.



PRICE LIST							
Code	Description	Capacity	Flow rate				
PFTF-3C70BS/A1X	TANK-FUEL APPROVED It. 3.000 with basin 110% mod. CUBE 70BS-without roof	3.000 lt.	72 lt/min				
PFTF-5C70BS/A1X	TANK-FUEL APPROVED It. 4.992 with basin 110% mod. CUBE 70BS-without roof	4.992 lt.	72 lt/min				
PFTF-7C70BS/A1X	TANK-FUEL APPROVED It. 7.000 with basin 110% mod. CUBE 70BS-without roof	7.000 lt.	72 lt/min				
PFTF-9C70BS1X	TANK-FUEL APPROVED It. 9.000 with basin 110% mod. CUBE 70BS-without roof	9.000 lt.	72 lt/min				

		ACCESSORIES OF	ACCESSORIES ON DEMAND			
Code Desc	Description	Code	Description			
PFTT-3000/A1X	ROOF FOR TF 3000/A 1X	ACGR-P/BS10AC	DRIVER ACCESS (X10)			
	ROOF FOR TF 5000/A 1X	ACTF/FILSEP60	WATER SEPARATOR FILTER (60 LTS/MINS)			
	ROOF FOR TF 7000/A 1X	ACGR-P/TB55/R	SURCHARGE ON ADDITIONAL HOSE			
PFTT-90001X	ROOF FOR TF 9000/A 1X	ACTF-FILWC*	WATER SEPARATOR FILTER CLEAR CAPTOR WC 30 MN			
		ACTF-FILCC*	IMPURITY FILTER CLEAR CAPTOR 5MN			



With CUBE B.SMART you have a hardware system with integrated software, completely managed in the Cloud. No complex installation on PC is required: B.SMART works in the cloud to allow you to manage your fleet from anywhere and monitor all fuel transactions

* FILTERS WITH TRANSPARENT SHELL, BLEED VALVE AND ADDITIONAL CARTRIDGE(SPARE)