

TANK FUEL DW APPROVED

vertical double wall fuel tanks



Tutte le immagini sono meramente a scopo illustrativo. L'azienda si riserva di apportare qualsiasi tipo di modifica senza alcuna comunicazione e/o autorizzazione

DIMENSIONS/WEIGHT

Code	Capacity	Diameter	Total height	Weight Kg
PFTFD-995P80	995 liters	1.120mm	1.777mm	300 kg
PFTFD-1.6P80	1.600 liters	1.300 mm	1.906 mm	430 kg
PFTFD-2P80	2.000 liters	1.300 mm	2.400 mm	525 kg
PFTFD-3P80	3.000 liters	1.620 mm	2.180 mm	610 kg
PFTFD-4P80	4.000 liters	1.970 mm	2.000 mm	720 kg
PFTFD-5P80	5.000 liters	1.970 mm	2.256 mm	795 kg
PFTFD-6P80	6.000 liters	1.970 mm	2.500 mm	850 kg
PFTFD-7P80	7.000 liters	2.270 mm	2.350 mm	980 kg
PFTFD-8P80	8.000 liters	2.270 mm	2.600 mm	1.020 kg
PFTFD-9P80	9.000 liters	2.270 mm	2.800 mm	1.100 kg

Double wall diesel Tanks P80, homologated by the Ministry of Internal Affairs according to Italian law n. 3704/1671-37/122

Steel tanks for Diesel fuel storage and delivery, homologated by Italian Ministry of Interior according D.M. 22 Novembre 2017. They are vertical, space-saving double-chamber tanks equipped with dispensing systems. The inner chamber is used to store diesel, while the watertight external chamber (safety tank), with continuous monitoring, guarantees the recovery of any product leaks and / or spills, according to the provisions of the D.M. 22/11/2017 for fire prevention purposes

The tanks are made of S235JR carbon steel according to the UNI EN 10025-2 standard, 3mm thick and treated externally with a metallic gray paint cycle. They are equipped with 1" internal suction pipe with non-return valve with calibrated spring, suction filter, 1" ball valve, 400 manhole type diesel fuel with 3" load with brass bayonet quick coupling with load limiting valve at 90%, enclosed in an anti-spill box with hinged padlockable lid, 1" 1/2 vent with brass flame cap, mechanical floating level indicator, pump blocking device at minimum level, electrical panel, plug for the connection of the earth cable, sight glass for checking the cavity, ball valve for emptying the cavity, with operating lever with key safety lock, access ladder to the manhole with non-slip steps according to safety standards and containment tray for any leaks from the dispensing unit.



Mechanical dispensing system:

P72 key locked metal cabinet which holds a self-priming electric pump fitted with by-pass valve (flow-rate 72lt/min). It is provided with a mechanic oscillating disk litre counter, automatic nozzle connected to a 4mt hose, electric panel with an emergency stop and a control chip for the level probe (pump blocks at the minimum level).

OPTIONAL



PRICE LIST

Code	Description	Capacity	Flow rate
PFTFD-995P80	DW TANK-FUEL APPROVED Its. 995 double wall fuel tank mod. P72	995 lts	72 lt/min
PFTFD-1.6P80	DW TANK-FUEL APPROVED Its. 1.600 double wall fuel tank mod. P72	1.600 lts	72 lt/min
PFTFD-2P80	DW TANK-FUEL APPROVED Its. 2.000 double wall fuel tank mod. P72	2.000 lts	72 lt/min
PFTFD-3P80	DW TANK-FUEL APPROVED Its. 3.000 double wall fuel tank mod. P72	3.000 lts	72 lt/min
PFTFD-4P80	DW TANK-FUEL APPROVED Its. 4.000 double wall fuel tank mod. P72	4.000 lts	72 lt/min
PFTFD-5P80	DW TANK-FUEL APPROVED Its. 5.000 double wall fuel tank mod. P72	5.000 lts	72 lt/min
PFTFD-6P80	DW TANK-FUEL APPROVED Its. 6.000 double wall fuel tank mod. P72	6.000 lts	72 lt/min
PFTFD-7P80	DW TANK-FUEL APPROVED Its. 7.000 double wall fuel tank mod. P72	7.000 lts	72 lt/min
PFTFD-8P80	DW TANK-FUEL APPROVED Its. 8.000 double wall fuel tank mod. P72	8.000 lts	72 lt/min
PFTFD-9P80	DW TANK-FUEL APPROVED Its. 9.000 double wall fuel tank mod. P72	9.000 lts	72 lt/min

ACCESSORIES ON DEMAND

Code	Description
ACTF/FILSEP60	WATER SEPARATOR FILTER (60lt/min))
ACGR-P/TB55/R	SURCHARGE FOR ADDITIONAL HOSE
ACTF-MONTK600	DIGITAL FLOW METER K600 ASSEMBLING
ACTF-FILWC*	CLEAR CAPTOR FILTER WC WATER SEP. 30 mn
ACTF-FILCC*	CLEAR CAPTOR FILTER CC IMPURITY 5 mn

* FILTERS WITH TRANSPARENT SHELL, BLEED VALVE AND ADDITIONAL CARTRIDGE(SPARE)

TFDC-P80